

ADVANTAGES®

Perfect. Everywhere.

EXTENSIVE RANGE

Extensive range of applications for Rockwheel cutting units.

GEAR RATIO

Gearred cutting units with a gear ratio of up to 2:1 for maximum torque – invented and unrivalled

MOTOR PROTECTION

Valve technology protects the hydraulic motor

RUNS WITHIN HAMMER CIRCUIT

Only two hydraulic connections – no case drain line required

SILENT OPERATION

Perfect for noise sensitive areas

LONGEST EXPERIENCE ON THE MARKET

Developed by Webster Technologies

REUSABLE CRUSHED MATERIAL

Crushed material with a diameter of 3 cm

LOWER VIBRATIONS

For cutting in sensitive and urban locations without transmitting vibrations to the surroundings

OPTIMAL PICK LACING

Maximum performance and smooth operations

SHORT DESIGN

Optimized transmission of power from the excavator to the Rockwheel

OPTIMIZED

POWER-TO-WEIGHT RATIO

Enhanced performance achieved with less weight

EXTREMELY HEAVY-DUTY

For the toughest jobs

STRENGTH OF MATERIALS (MPa)



soft material
(up to 10)



medium to hard material
(10 to 100)



hard material
(100 to 200)



extremely hard material
(over 200)